

Adobe.AD0-E116.v2023-08-07.q31

Exam Code:	AD0-E116
Exam Name:	Adobe Experience Manager Developer Expert
Certification Provider:	Adobe
Free Question Number:	31
Version:	v2023-08-07
# of views:	928
# of Questions views:	310
https://www.exam-tests.com/AD0-E116-exam/Adobe.AD0-E116.v2023-08-07.q31.html	

NEW QUESTION: 1

Which environment variable in the AEM start script should a developer modify to enable remote debugging?

- A. CQ_RUNMODE
- B. CQ_HOST
- C. CQ_PORT
- D. CQ_JVM_OPTS

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 2

A developer needs to ensure that the path /content/<proj>/segments exists on all environments with the correct initial content that the developer provides in a package. Content that exists in that path should NOT be affected.

Which import mode should the developer use in the filter definition?

- A. merge
- B. optional
- C. update
- D. replace

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 3

A developer running a local AEM instance and working on an AEM project needs to change a large number of files locally in filesystem. The developer needs to get the changes uploaded to the local AEM instance to verify changes almost immediately in the browser.

What action should the developer take to most efficiently meet these requirements?

- A. Build a Content Package using maven and deploy it after each change
- B. Install FileVault bundle in the AEM instance and register the local working directory for synchronization
- C. Make the changes in CRXDE, create a content package, download it and expand it into the working directory after each change
- D. Access CRXDE and upload the files through the interface

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 4

An application runs specific license checks against certain DAM assets every day. It should send an email to a configured list if it finds warnings, and mark the asset accordingly. A service component that uses the Apache Sling Scheduler Service is created. DAM assets that must NOT be used anymore are hidden using ACLs and the license check must re-check them.

How should a developer obtain a resource resolver that can read and update the DAM assets?

- A. Create a configuration line in PID `com.day.cq.security.ACLSetup` for the user that you obtain a session for via `ResourceResolverFactory.getResourceResolver(...)`.
- B. Configure the user `admin` in PID `org.apache.sling.serviceusermapping.impl.ServiceUserMapperImpl` as `user.default` and make sure the service user exists and has `jcr:read` and `jcr:write` permissions.
- C. Create a configuration for PID `org.apache.sling.serviceusermapping.impl.ServiceUserMapperImpl.amended-damaccess` that references a pre-created service user with r/w permissions and use `ResourceResolverFactory.getServiceResourceResolver(...)`.
- D. Set up a cron job with curl calls with the admin user and use `request.getResource().getResourceResolver()`.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 5

A developer needs to install a content package on an AEM environment. However a content package with the same name is already installed.

What would be the safest way for the developer to install the content package to make sure only the changes of the new content package get applied?

- A. Upload the content package to the CRX Package Share before installing it
- B. Use the "Force Upload" option when uploading the new content package
- C. Install the content package using the OSGi web console
- D. Uninstall the existing content package before installing the new content package

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 6

There is a config file `package.myClass.config.factory-myApp.xml` - what is true? (Choose two)

- A. Should be set `package.myClass.config.factory-<identifier>`
- B. Must be set `package.myClass.config.factory-<identifier>`
- C. The word "config" is a sign of factory
- D. The word "factory" is a sign of factory

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 7

A developer needs to implement a functionality that requires creating a Custom Workflow Step.

Which two steps should the developer take to start developing the custom behavior? (Choose two)

- A. Create a Workflow component node of the Super Resource Type `"cq/workflow/components/step"` under the folder `/etc/workflow/models`
- B. Implement a Java class implementing the interface `com.adobe.granite.workflow.exec.WorkflowProcess`
- C. Implement a Java class with this method `"public void process (WorkItem item, WorkflowSession wfsession) throws WorkflowException"`
- D. Implement a Java class extending from class `com.adobe.granite.workflow.exec.WorkflowProcess`

E. Create a Workflow component node of the Super Resource Type "cq/workflow/components/model/process" under the folder /apps/components

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 8

The custom AEM application needs to keep a flat list of all page paths underneath /content/thesite in memory for a real-time integration with high performance requirements.

The developer has the following intermediate state of the class:

```
@Component(immediate = true)
public class PagePathsCacheImpl implements PagePathsCache {
    @Reference
    ResourceResolverFactory resourceResolverFactory;
    List<String> pagePaths = new CopyOnWriteArrayList<String>();
    @Activate
    public void activate() {
        // ... here the initial state of pagePaths is filled via resourceResolver.findResources(...)
    }
    public List<String> getPagePaths() {
        return pagePaths;
    }
}
```

What action should the developer take to meet these requirements?

A

Make the class also implement `ResourceChangeListener` and add

```
property = {
    ResourceChangeListener.CHANGES + "=ADDED",
    ResourceChangeListener.CHANGES + "=REMOVED",
    ResourceChangeListener.PRIMARY_TYPES + "=cq:Page"
    ResourceChangeListener.PATHS + "=/content/thesite"
}
```

to the `@Component` annotation. In method `onChange` update field `pagePaths` according to received list of `ResourceChange`.

B

Make the class also implement `ResourceChangeListener` and add

```
property = {
    ResourceChangeListener.CHANGES + "=ADDED",
    ResourceChangeListener.CHANGES + "=REMOVED",
    ResourceChangeListener.PATHS + "=/content/thesite"
}
```

to the `@Component` annotation. In method `onChange` filter received list of `ResourceChange` for pages only and update field `pagePaths` accordingly.

C

Make the class also implement ResourceObservationManager and add

```
property = {
    ResourceObservationManager.CHANGES + "=ADDED",
    ResourceObservationManager.CHANGES + "=CHANGED",
    ResourceObservationManager.CHANGES + "=REMOVED",
    ResourceObservationManager.PATHS + "=/content/thesite"
}
```

to the @Component annotation. In method onChange filter received list of ResourceChange for pages only and adjust field pagePaths accordingly.

D

Make the class also implement ResourceObservationManager and add

```
property = {
    ResourceObservationManager.CHANGES + "=ADDED",
    ResourceObservationManager.CHANGES + "=REMOVED",
    ResourceObservationManager.PRIMARY_TYPES + "=cq:Page"
    ResourceObservationManager.PATHS + "=/content/thesite"
}
```

to the @Component annotation. In method onChange update field pagePaths according to received list of ResourceChange.

A. Option C

B. Option A

C. Option B

D. Option D

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 9

A developer needs to create a banner component. This component shows an image across the full width of the page. A title is shown on top of the image. This text can be aligned to the left, middle, or right. The core components feature a teaser component which matches almost all requirements, but not all.

What is the most maintainable way for the developer to implement these requirements?

A. Use and configure the teaser core component.

B. Create a new custom component from scratch.

C. Overlay the teaser core component.

D. Inherit from the teaser core component.

Answer: D ([LEAVE A REPLY](#))

Reference:

<https://docs.adobe.com/content/help/en/experience-manager-core-components/using/components/teaser.html>

NEW QUESTION: 10

A developer has a component foofoo that consists of the files listed below:

script-a.js

```
"use strict";
use(function () {
    return "foo";
});
```

script-b.js

```
"use strict";
use(function () {
    return "";
});
```

foofoo.html

```
<div data-sly-use.a="script-a.js" data-sly-use.b="script-b.js">
  <div data-sly-attribute.class="{a}" class="bar"></div>
  <div class="bar" data-sly-attribute.class="{a}"></div>
  <div class="foo" data-sly-attribute.class="{b}"></div>
  <div data-sly-attribute.class="{a}"></div>
</div>
```

What is the output when this component is rendered?

```

<div>
  <div class="bar"></div>
  <div class="foo"></div>
  <div></div>
  <div></div>
</div>

```

```

<div>
  <div class="bar"></div>
  <div class="foo"></div>
  <div></div>
  <div class=""></div>
</div>

```

```

<div>
  <div class="foo"></div>
  <div class="foo"></div>
  <div class=""></div>
  <div class="foo"></div>
</div>

```

D

```

<div>
  <div class="bar"></div>
  <div class="bar"></div>
  <div class="foo"></div>
  <div class=""></div>
</div>

```

- A. Option B
- B. Option A
- C. Option D
- D. Option C

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 11

After adding new features, a developer's environment is experiencing slowness before ultimately running out of memory. The initial log analysis points towards a large number of open sessions.

Which action should the developer take to further monitor the overall session count on this AEM instance?

- A.** Run the following command to generate thread dumps `jstack -l <pid> >> threaddumps.log`, analyze thread dumps to find long running sessions.
- B.** Go to Web Console > Status > Threads, verify the overall thread count.
- C.** Go to `<aem-install>/crx-quickstart/logs/stderr/log`, use the following command `grep -o 'CRXSessionImpl' stderr.log | wc -l`.
- D.** Go to Tools > Operations > Monitoring. Create a new report based on Number of Active Sessions as metric.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 12

A developer has a component located under the path `/apps`. This component has a Client Library which is directly loaded onto a page. The publish instance loads the page correctly. The dispatcher also loads the page but the Client Library is missing.

How should the developer resolve this issue, while taking security into consideration?

- A.** Add the property `allowProxy` with a boolean value `true`.
- B.** Allow the path to the clientlibs on the dispatcher.
- C.** Change the ACLs for the Client Library.
- D.** Move the Client Library under `/apps/<project>library`.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 13

A developer is working on a project locally and needs to install packages manually. The deployments to the localhost must be automated to speed up development. This functionality must be toggled on and off, depending on the needs of the developer.

Which step should the developer take to achieve this?

- A.** Run maven with the `deploy` phase. Maven will install the package on all local AEM instances running without further configuration
- B.** Write a script that does a `PUT` call to AEM each time maven builds a new package
- C.** Configure the maven install plugin by defining the target URL, username and password as maven properties.
- D.** Add a maven profile and configure the content package maven plugin within this profile

Answer: **D** ([LEAVE A REPLY](#))

NEW QUESTION: 14

A developer wants to change the log level for a custom API.

Which OSGi configuration should the developer modify?

- A.** Apache Sling Log Tracker Service
- B.** Adobe Granite Log Analysis Service
- C.** Apache Sling Logging Writer Configuration
- D.** Apache Sling Logging Configuration

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 15

A developer needs to create an OSGi service to run on an Author instance and send out newsletters at periodic intervals. Intervals should be customized using the Web Console Configuration. Concurrent execution must be prevented.

Which code snippet should a developer use to achieve?

```

@Component(service = Runnable.class)
@Designate(ocd = SendEmailNewsletterImpl.Config.class)
public class SendEmailNewsletterImpl implements Runnable {

    @ObjectClassDefinition(name = "A simple cleanup task", description =
"Simple demo for cron-job like task with properties")
    public static @interface Config {

        @AttributeDefinition(name = "Cron-job expression")
        String scheduler_expression() default "*/30*+*+*?";

        @AttributeDefinition(name = "Configure task", description =
"Whether or not to schedule this task concurrently")
        boolean scheduler_concurrent() default false;

        @AttributeDefinition(name = "A parameter", description =
"Can be configured in /system/console/configurMgr")
        String myParameter() default "";
    }
}

```

```

@Component (immediate=true, service = Servlet.class, property = {Constants.SER
VICE_DESCRIPTION + "=Send Newsletter Sling Servlet",
        "sling.servlet.method=" + HttpConstants.METHOD_PUT,
        "sling.servlet.concurrent=" + "false",
        "sling.servlet.interval=" + "*/30*+*+*?"
    })
public class SendNewsletterServlet extends SlingSafeMethodsServlet {

    ....
}

```

```

@Component (immediate=true,
enabled=true,
service = Importer.class,
property = {
        Importer.concurrent + "=false",
        Importer.interval + "*/30*+*+*?"
    })
public class SendEmailNewsletterImpl implements Importer {

    ....
}

```

D

```
@Component(service = EventHandler.class,
            immediate = true,
            property = {
                Constants.SERVICE_DESCRIPTION + "=Send NewsLetter",
                EventConstants.EVENT_TOPIC + "=org/apache/sling/api/
resource/Resource/*",
                EventConstants.interval + "=
*/30****?"
            })
public class SendNewsletterListener implements EventHandler {
    boolean isConcurrent = false;
    String interval = "*/30****?"
    public void handleEvent(final Event event) {
        event.send(isConcurrent, event.getTopic(), interval);
    }
}
```

- A. Option B
- B. Option C
- C. Option D
- D. Option A

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 16

Which xml tag is used within the vault package definition to add a new path to a content package?

- A. <content>
- B. <path>
- C. <filter>
- D. <rule>

Answer: C ([LEAVE A REPLY](#))

Valid AD0-E116 Dumps shared by BraindumpsPass.com for Helping Passing AD0-E116 Exam! BraindumpsPass.com now offer the **newest AD0-E116 exam dumps**, the BraindumpsPass.com AD0-E116 exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com AD0-E116 dumps with Test Engine here:

<https://www.braindumpsPass.com/Adobe/AD0-E116-practice-exam-dumps.html> (95 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 17

A custom AEM application has a run time dependency to a third party OSGi bundle that is NOT included in out-of-the-box AEM. The third party dependency needs to be available for multiple applications and be upgraded separately from the custom AEM application.

How should a developer make sure that the bundle is installed on all environments?

- A. Add the dependency to the third party bundle in pom.xml of the project bundle
- B. Embed the bundle in a content package to have it automatically deployed
- C. Declare the dependency correctly using a link to the OSGi Bundle Repository (OBR)
- D. Embed the third party bundle in the bundle that depends on it

Answer: [\(SHOW ANSWER\)](#)

NEW QUESTION: 18

A developer creates a template-type for building editable templates.

The resulting editable templates and pages must always contain a specific layout container that can NOT be deleted by the author.

How should the developer meet this requirement?

- A. Add the layout container component to the initial section of the template-type
- B. Add the layout container component by including it on the actual page component
- C. Add the layout container component to the structure section of the template-type
- D. Add a content policy to the template-type to disable the removal of the layout container

Answer: A [\(LEAVE A REPLY\)](#)

NEW QUESTION: 19

A custom AEM application is using the PageManager API.

What should a developer add to make the application compile and run correctly in AEM?

- A. a maven dependency to bundle cq-wcm-api to the content package
- B. a maven dependency to AEM uber-jar to the application bundle
- C. a maven dependency to bundle cq-wcm-core to the application bundle
- D. a maven dependency to AEM uber-jar to the content package

Answer: B [\(LEAVE A REPLY\)](#)

NEW QUESTION: 20

A developer needs to change the label "Sites" in the navigation of AEM author to "Websites".

Which action should the developer take to achieve this?

- A. Change the code of /libs/granite/ui/components/shell/clientlibs/shell/js/globalnav.js to display the new value
- B. Create a new node /apps/cq/core/content/nav/sites and update the property jcr:title
- C. Modify the node /libs/cq/core/content/nav/sites by updating the jcr:title property
- D. Modify the code of /libs/granite/ui/components/shell/globalnav/overlay/overlay.jsp to display the new value

Answer: B [\(LEAVE A REPLY\)](#)

NEW QUESTION: 21

A custom application contains a service component com.proj.ServiceComponent. A developer needs to configure the string value name and integer value intVal. The actual configuration must be deployed using a content package.

What should the developer do to meet these requirements?

A. "Use a file com.proj.ServiceComponent.xml with content

```
<?xml version=""1.0"" encoding=""UTF-8""?>
<jcr:root jcr:primaryType=""sling:OsgiConfig""
name=""Service Name""
intVal=""5""/>
```

B. "Use a file com.proj.ServiceComponent.cfg with content

```
name=""Service name""
intVal=|""5""
```

C. "Use a file com.proj.ServiceComponent.xml with content

```
<?xml version=""1.0"" encoding=""UTF-8""?>
<jcr:root xmlns:jcr=""http://www.jcp.org/jcr/1.0"" jcr:primaryType=""sling:OsgiConfig"" name=""Service Name"" intVal=""{Integer}5""/>
```

D. "Use a file com.proj.ServiceComponent.config with content

```
name=""Service name""
intVal=|""5""
```

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 22

A developer creates an AEM editable template that includes a Layout Container. When the developer creates a page using this template, the Layout Container placeholder does NOT appear.

What is causing this issue?

A. The page template has NOT been enabled.

B. The Layout Container has NOT been unlocked.

C. The Layout Container does NOT have a policy.

D. The page template has NOT been published.

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 23

How should a developer enable remote debugging of an AEM server without modifying the AEM start script?

A. Rename the quickstart jar file to include the additional debug settings.

B. Enable the remote debugging service through the AEM Cloud Services menu.

C. Include an additional JVM parameter when starting AEM with java -jar.

D. Enable the remote debugging service through the AEM Web Console.

Answer: (SHOW ANSWER)

NEW QUESTION: 24

A developer creates a custom component. The component dialog includes the following two fields:



text

- jcr:primaryType="nt:unstructured"
- sling:resourceType="granite/ui/components/coral/foundation/form/textarea"
- fieldlabel="Text"
- name="./text"

charLimit

- jcr:primaryType="nt:unstructured"
- sling:resourceType="granite/ui/components/coral/foundation/form/numberfield"
- defaultValue="0"
- fieldlabel="Character Limit"
- name="./charLimit"

he component should display the first 'X' characters of the text entered in the 'text' input where 'X' is the number entered in the 'charLimit' input. If zero, or no value, is entered in the 'charLimit' input then the text should be unaltered. The developer creates the following Sling Model to perform the truncation:

```

java
@Model(adaptables = SlingHttpServletRequest.class, defaultInjectionStrategy = DefaultInjectionStrategy.OPTIONAL)
public class Truncation {

    @ValueMapValue
    private String text;

    @ValueMapValue
    private Integer charLimit;

    @PostMapValue
    private void init() {
        if (text != null && 0 < charLimit && charLimit < text.length()) {
            text = text.substring(0, charLimit);
        }
    }

    public String getText() {
        return text;
    }
}

```

A Null Pointer Exception occurs if NO charLimit values is set in the component dialog.

What should the developer do to resolve this issue?

- A. Replace the defaultValue="0" attribute of the charLimit field in the dialog with defaultValue="{Long}0".
- B. Change the defaultInjectionStrategy of the Truncation Sling Model to DefaultInjectionStrategy.REQUIRED.
- C. Add the @Default annotation to the 'charLimit' variable in the Sling Model.
- D. Replace the defaultValue="0" attribute of the 'charLimit' field in the dialog with min="0".

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 25

A developer developed a workflow that makes a copy of every node created or modified under a certain path to a different one. The workflow launches but the nodes are not copied over.

Which two methods should the developer use to resolve this issue? (Choose two.)

- A. Go to Workflow Failures screen and check if any instances of the workflow are present.
- B. Go to Workflow instances screen and verify that the instance of the workflow is present and check its status.
- C. Go to Workflow Models screen, then delete and recreate the workflow.
- D. Go to Package Manager screen and reinstall the bundle that contains the workflow so it restarts.
- E. Go to Workflow Launchers and create a new launcher for the workflow even if one already exists.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 26

Which log file contains AEM application request and response entries?

- A. response.log
- B. history.log
- C. request.log
- D. audit.log

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 27

A developer is creating a new OSGi bundle com.custom.package.b to expose new services.

com.custom.package.a is already installed and active in the system and has the following package definition:

```
Export-Package: com.custom.package.a;version="2.0"
Import-Package: com.sample.package.a;version="[1,2)"
Classpath: .,com.sample.package.b-3.0.jar
```

The system console shows the following package availability:

```
com.sample.package.a;version="1.5"
com.sample.package.c;version="3.0"
```

Bundle com.custom.package.b to be installed has the following package definition:

```
Export-Package: com.custom.package.b;version="1.0"
Import-Package: com.custom.package.a;version="[1,2)",com.sample.package.b;version="[3.0,3.0)",com.sample.package.c;version="[2,3)
```

What will happen when the developer uploads the bundle com.custom.package.b into the system?

- A. The bundle will install but fail the activation due to unsatisfied dependency com.sample.package.c.
- B. The bundle will install and activate successfully.
- C. The bundle will install but fail the activation due to unsatisfied dependency com.sample.package.b.
- D. The bundle will install but fail the activation due to unsatisfied dependencies com.sample.package.b and com.sample.package.c.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 28

The developer is presented with a component "Component A" which inherits from a component "Component B".

The dialog of Component A on path ../cq:dialog/../../items looks like:

- + align
- jcr:primaryType="nt:unstructured"
- sling:resourceType="granite/ui/components/coral/foundation/form/select"
- fieldLabel="Align Text"
- name="./align"

The dialog of Component B on path ../cq:dialog/../../items looks like:

- + title
- jcr:primaryType="nt:unstructured"

- sling:resourceType="granite/ui/components/coral/foundation/form/textarea"
- fieldLabel="Title"
- name="/title"
- + description
- jcr:primaryType="nt:unstructured"
- sling:resourceType="granite/ui/components/coral/foundation/form/textarea"
- fieldLabel="Description"
- name="/description"

The requirement for the dialog is that the **Align Text** field is shown after the **Title** field.

What should the developer do without changing Component B?

- A.** Move the align node from Component A to Component B and order them according the requirements.
- B.** Add the property sling:orderBefore="description" to the align node.
- C.** Extend Component B with the functionality of Component A
- D.** Move all the nodes under the item node from Component B to Component A and order them according the requirements.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 29

A custom AEM application contains a service component that needs to access the JCR repository within the activate method. The activate method uses ResourceResolverFactory.getServiceResourceResolver(...) without specifying a sub service name.

What should a developer do to make sure the user service mapping for the service component is available?

- A.** Create a field of type ServiceUserMapped and annotate it with @Reference
- B.** Create a field of type ServiceUserMapped and annotate it with @Reference using ReferencePolicy.DYNAMIC
- C.** Wait for the service ServiceUserMapper via BundleContext.getServiceReference(...)
- D.** Create a field of type ServiceUserMapper and annotate it with @Reference using ReferencePolicy.STATIC

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 30

An application contains an OSGi configuration that contains a password.

How should a developer prevent this sensitive information from being stored in plain text in JCR?

- A.** 1. Use console at /system/console/crypto to encrypt the value
- 2. Either create an encrypted value for each AEM instance and use runmodes to apply the different values or make sure relevant instances share the same master key
- 3. Sensitive information is automatically decrypted using the CryptoSupport OSGi service before the value is returned
- B.** 1. Use console at /system/console/configMgr and tick the checkbox "encrypt" before saving a configuration
- 2. Either create an encrypted value for each AEM instance and use runmodes to apply the different values or make sure relevant instances share the same master key
- 3. Sensitive information is automatically decrypted using the CryptoSupport OSGi service before the value is returned
- C.** 1. Use console at /system/console/crypto to encrypt the value
- 2. Either create an encrypted value for each AEM instance and use runmodes to apply the different values or make sure relevant instances share the same master key
- 3. When loading the value in the code, call CryptoSupport.unprotect(_) before using the value

- D. 1. Use console at /system/console/configMgr and tick the checkbox "encrypt" before saving a configuration
2. Use encrypted values work across all instances
3. When loading the value in the code, call CryptoSupport.unprotect(...) before using the value

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 31

A developer creates Editable Templates based on a custom Page component. The developer wants to leverage the Style System within the Editable Templates to allow authors to switch between the Dark and Light Theme. The Style System dialog is NOT enabled for the site.

What should the developer do to resolve this issue?

- A. Create two new client libraries with a dark and light theme and map them to the Page component.
B. Define Style Definitions using Page Policy dialog on Editable Template.
C. Create a new dialog for the custom Page components.
D. Set the sling:resourceSuperType property to core/wcm/components/page/v2/page on the Page component.

Answer: ([SHOW ANSWER](#)**)**

Valid AD0-E116 Dumps shared by BraindumpsPass.com for Helping Passing AD0-E116 Exam! BraindumpsPass.com now offer the **newest AD0-E116 exam dumps**, the BraindumpsPass.com AD0-E116 exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com AD0-E116 dumps with Test Engine here:

<https://www.braindumpspass.com/Adobe/AD0-E116-practice-exam-dumps.html> (95 Q&As Dumps, **40%OFF** Special Discount:

Exam-Tests)

Valid AD0-E116 Dumps shared by BraindumpsPass.com for Helping Passing AD0-E116 Exam! BraindumpsPass.com now offer the **newest AD0-E116 exam dumps**, the BraindumpsPass.com AD0-E116 exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com AD0-E116 dumps with Test Engine here:

<https://www.braindumpspass.com/Adobe/AD0-E116-practice-exam-dumps.html> (95 Q&As Dumps, **40%OFF** Special Discount:

Exam-Tests)