

Huawei.H12-821_V1.0-ENU.v2022-08-12.q128

Exam Code:	H12-821_V1.0-ENU
Exam Name:	HCIP-Datacom-Core Technology V1.0
Certification Provider:	Huawei
Free Question Number:	128
Version:	v2022-08-12
# of views:	4254
# of Questions views:	1280
https://www.exam-tests.com/H12-821_V1.0-ENU-exam/Huawei.H12-821_V1.0-ENU.v2022-08-12.q128.html	

NEW QUESTION: 1

For the information output by the display ospf peer, which of the following description is true?

<Huawei=display ospf peer

OSPF Process 1 with Router ID 10.1.1.2

Neighbors

Area 0.0.0.0 interface 10.1.1.2(Gigabitethernet1/0/0)'s neighbors

Router ID: 10.1.1.1

Address:10.1.1.1

State: Full Mode: Nbr is Slave Priority: 1

DR: 10.1.1.1BDR: None MTU: 0

Dead timer due in 38 sec

Retrans timer interval: 5Neighbor is up for 00: 00:04

Authentication Sequence: [0]

A. Address: 10.1.1.1 means the local interface address is 10.1.1.1

B. Designated router (DR) for the address is 10.1.1.1

C. Router ID means that the local router ID is 10.1.1.1

D. After negotiation during the DD exchange process, the local end becomes a slave

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 2

Which of the following tools cannot be directly referenced by the apply clause of route-policy?

A. day

B. origin

C. community

D. IP-Prefix

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 3

Regarding the description of IBGP neighbors and EBGP neighbors, which of the following is false?

- A. If the two exchange BGP packets peers belong to different autonomous systems, then the two peers are EBGP peer
- B. If the two exchange BGP packets peers in the same autonomous system, then the two peers are IBGP peer
- C. IBGP peers must be physically directly connected
- D. Two routers running BGP must have IP connectivity to establish a TCP session

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 4

In the MAC-based Portal authentication scenario, when a user successfully performs Portal authentication, he can disconnect from the network and reconnect within a certain period of time, and he can directly access through MAC authentication without entering the username and password to perform Portal authentication again.

- A. TRUE
- B. FALSE

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 5

Which description is correct about the characteristics of a high-availability network? (Multiple choice)

- A. No failure
- B. Once a failure occurs, the business can only be restored through manual intervention
- C. Do not fail frequently
- D. Can recover quickly after failure

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 6

Which of the following statement about the IS-IS protocol is wrong?

- A. IS-IS protocol supports IP network
- B. The Is-Is protocol is a link state protocol running between ASs
- C. IS-IS protocol supports CLNP network
- D. IS-IS protocol packets are directly encapsulated by the data link layer

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 7

RTA is the source DR router and RIB is the RP router. The multicast source sends multicast data to RTA, but the multicast source registered with it through the PIMRegister message cannot be seen on the RIB. What are the possible reasons? (Multiple choice)

- A. There is no single-point route from RTB to RTA, which causes RIB's RPF check of the source to fail
- B. The multicast network is statically configured with RP, but the RTA router is not statically configured with RP
- C. The multicast network dynamically elects the RP, but the RTA's RPF check on the BSR fails
- D. The RP elected by RTA is not RTB

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 8

Which statements are correct about the VRRP protocol version? (Multiple choice)

- A. VRRPv3 is only applicable to IPv6
- B. VRRPv2 is only applicable to IPv4
- C. VRRPv2 supports authentication
- D. VRRPv3 does not support authentication

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 9

The output information of a router below, which of the following regarding the description of this information is true?

- A. The next hop of the route to the target network 1.1.1.0/24 is 1.1.1.1, and the route is optimal
- B. The MED value of the route to the destination network 5.1.1.0/24 is 50
- C. The next hop of the route to the target network 5.1.1.0/24 is 1.1.1.1, and the route is optimal
- D. The MED value of the route to the destination network 1.1.1.0/24 is 100

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 10

A VRRP virtual router can only have a virtual IP address.

- A. True
- B. False

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 11

What are the differences between IGMP versions? (Multiple choice)

- A. IGMPv1/v2/v3 cannot support the SSM model
- B. IGMPv1/v2 cannot elect a querier by itself, while IGMPv3 can
- C. For members to leave, IGMPv2/v3 can leave voluntarily, but IGMPv1 cannot
- D. IGMPv1 does not support specific group queries, while IGMPv2 supports

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 12

The following information is the output of a router, which of the following regarding the information is true?

- A. The community attribute value carried by the destination network segment 1.1.1.0/24 is no-export, indicating that the route entry can be advertised to any BGP neighbor
- B. The community attribute value carried by the destination network segment 5.1.1.0/24 is no-advertise, indicating that the route entry cannot be advertised to any other BGP peers
- C. The community attribute value carried by the destination network segment 1.1.1.0/24 is no-export, indicating that the route entry cannot be advertised to any BGP neighbors
- D. The community attribute value carried by the destination network segment 5.1.1.0/24 is no-advertise, indicating that the route entry cannot be advertised outside the local AS

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 13

After dividing an interface of the firewall into the Untrust security zone, the interface belongs to the Untrust zone and no longer belongs to the Local zone

- A. TRUE
- B. FALSE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 14

The command to configure VRRP to track the state of the physical interface is.

- A. vrrp vrid 1 interface Gigabitethernet0/0/0 track
- B. vrrp vrid 1 track interface Gigabitethernet0/0/0
- C. track vrrp vrid 1 interface Gigabitethernet0/0/0
- D. vrrp vrid 1 interface Gigabitethernet0/0/0

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 15

The RSTP protocol defines different port states, including Discarding and Learning. Which descriptions of these two port states are correct? (Multiple choice)

- A. Ports in the Discarding state and the learning state do not learn the MAC address table
- B. Ports in the Learning state do not learn the MAC address table
- C. The port in the Discarding state does not learn the MAC address table
- D. Ports in these two states do not forward data frames

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 16

In a large-scale WLAN network, if the VLAN Pool uses HASH to allocate VLAN, the number of users in each VLAN will be evenly divided.

A. FALSE

B. TRUE

Answer: A ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpsPass.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 17

Which routes among the following options satisfy the following ACL parents? (Multiple choice)

[HUAWEI] acl number 2001

[HUAWEI-acl-basic- 2001] rule 0 permit source 10.1.1.0 0.0.254.255

A. 10.1.3.1/32

B. 10.1.1.1/32

C. 10.1.4.1/32

D. 10.1.2.1/32

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 18

Which of the following description of VRRP is wrong?

A. When two routers with the same priority compete for the Master at the same time, compare the size of the interface IP address, and the one with the larger interface address is elected as the Master

B. If the Backup router works in non-preemptive mode, as long as the Master router does not fail, the Backup router will not become the Master router even if it is subsequently configured with a higher priority.

C. VRRP determines the status of each router in the virtual router based on priority

D. If the Master already exists, Backup will also preempt.

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 19

Which of the following description about verifying whether a received Hello message is legal is wrong?

A. The RouterDeadInterval field in the received Hello message must be consistent with the configuration of the receiving port

- B.** If the network type of the receiving port is a point-to-point type or a virtual link, the Network Mask field is not checked
- C.** If the network type of the receiving port is broadcast, point-to-multipoint or NBMA, the Network Mask field in the received Hello message may be inconsistent with that of the interface.
- D.** The E-bit in the Options field of the received Hello message must be consistent with the configuration of the relevant area

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 20

Compared with routers and switchies, what are the unique modules for firewall forwarding?

- A.** MPU
- B.** SPU
- C.** Switching network board
- D.** LPU

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 21

Regarding the OSPF protocol packets, which of the following statement is false?

- A.** The OSPF protocol uses five types of messages to complete the transmission of routing information
- B.** All OSPF packet headers carry the Router-ID field
- C.** The header format of all OSPF packets is the same
- D.** OSPF packets are encapsulated in UDP packets, and the port number is 89

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 22

Intranet users of a company use the No-pat method of NAT to access the Internet. If all public IP addresses are used, what will happen to intranet users who subsequently go online?

- A.** Synchronize packets to other NAT translation devices for NAT translation
- B.** Subsequent intranet users will not be able to access the Internet
- C.** Squeeze out the previous user and force the NAT conversion to go online
- D.** Automatically switch NAT to PAT and then surf the Internet

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 23

Which of the following description of the Hello message in PIM-SM is wrong?

- A.** Election of DR in multi-router network segment through Hello message
- B.** The Hello message is sent to the multicast address 224.0.0.5
- C.** In the PIM-SM network, the newly started multicast router needs to use Hello messages to discover neighbors and maintain neighbor relationships
- D.** The routers periodically use Hello messages to keep in touch

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 24

The route is injected into BGP through the network command. Which of the following description is wrong? (Multiple choice)

- A. The route must exist in the IP routing table and is the best route
- B. The length of the mask must match exactly
- C. The route cannot be an IGP route, it can only be a direct route
- D. Just match the prefix, the length of the mask does not need to be strictly matched

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 25

What is the sequence of the VLAN Pool assigning VLANs to the terminal? (Multiple choice)

- A. Assign VLAN to the terminal according to the VLAN algorithm
- B. Determine the VLAN Pool and VLAN algorithm bound to the VAP
- C. Terminal access to VAP
- D. The terminal accesses from the divided VLAN

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 26

OSPF supports multiple processes. Multiple different OSPF processes can run on the same router. They do not affect each other and are independent of each other. The routing interaction between different OSPF processes is equivalent to the routing interaction between different routing protocols.

- A. False
- B. True

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 27

How does IGMPv2 router maintain the network segment group membership? (Multiple choice)

- A. After receiving the leave message, the router immediately deletes the group membership
- B. The router maintains a timeout timer for each group membership, refreshes the timer if it receives the receiver host, and deletes the group membership if the timer expires
- C. The router will query a specific group
- D. The router periodically sends Query messages, and the receiver host reports a Repeat message after receiving the Query message

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 28

In PIM-DM, which combination of working mechanisms constructs SPT? (Multiple choice)

- A. State refresh

- B. Pruning
- C. Grafting
- D. Diffusion

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 29

There are many employees in an enterprise building, and they usually start to access the company's WLAN network in the lobby when they go to work. As each employee walks to their respective workstations, everyone's mobile terminal also roams to their respective network coverage areas by roaming.

In order to ensure that the IP address of each terminal is fixed as much as possible, what is the recommended approach?

- A. Configure VLAN Pool and configure sequential algorithm
- B. Configure VLAN Pool and configure Hash algorithm
- C. Without configuring VLAN Pool, configure a static IP address for each mobile terminal
- D. Configure VLAN Pool and configure the algorithm arbitrarily

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 30

The BGP protocol uses () messages to withdraw routing entries. (All lowercase in English)

Answer:

update

NEW QUESTION: 31

The RSTP mid-side port does not need to wait for the forwarding delay, and can directly enter the forwarding state. If the edge port receives the BPDU, the edge port will be directly closed and enter the Aerror-down state.

- A. False
- B. True

Answer: A ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpsPASS.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 32

When OSPF runs in a broadcast network, DR and BDR need to be elected.

Then in which of the following statements will DR and BDR elections be conducted?

- A. 2-way status
- B. Init status
- C. Exchange status
- D. Full state

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 33

VPN technology that can only provide Layer 2 network interconnection.

- A. FALSE
- B. TRUE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 34

Which of the following default route delivery methods does OSPF support? (Multiple choice)

- A. Can only be issued by force
- B. Can be issued non-mandatory
- C. Can be sent up and down in ABR
- D. Can be sent up and down in ASBR

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 35

Which of the following parameters are not necessary when configuring BGP Peer? (Multiple choice)

- A. description
- B. Password
- C. peer IP Address
- D. as number

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 36

What are the key components of building an IP wide area bearer network solution with Huawei NetEngine smart router?

- A. iMaster NCE-IP
- B. iMaster NCE-WAN
- C. iMaster NCE-Fabric
- D. iMaster NCE-Campus

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 37

Routes injected into BGP by re-issuing the command, the Origin attribute of which is Incomplete

A. FALSE

B. TRUE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 38

Which of the following description about configuration commands for the default routing issued by each protocol is wrong?

A. In the OSPF protocol, the default-route- advertised command is used to advertise the default route information to the normal OSPF area

B. In static routing, the ip route- static default preferencer command is used to generate a default route on the current router

C. In the ISIS protocol, the default-route-advertise command is used to advertise the default route information to neighbors

D. In the BGP protocol, the default-route imported command is used to enable the function of importing provincial routes into the BGP routing table

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 39

The BGP Speaker only advertises the changed routes to neighbors.

A. TRUE

B. FALSE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 40

Which of the following about the description of the information contained in the OPEN message in the EGP is incorrect?

A. OPEN message contains local AS number information

B. OPEN message contains VERSION information

C. OPEN message contains only BGP message header

D. OPEN message contains Hold time message

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 41

Which is wrong about the NDP address function in the following description?

A. When sending a neighbor solicitation message, the destination address must be the neighbor's solicited node multicast address

B. Two ICMPv6 messages, neighbor solicitation and neighbor advertisement, are used in the address process

C. When sending a neighbor solicitation message, the source address must be the link-local address of the local interface

D. The address realizes the function from the IPv6 address to the link layer address

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 42

Which of the following description of the information contained in the OPEN message in the EGP is wrong?

A. OPEN message contains local AS number information

B. OPEN message contains VERSION information

C. OPEN message contains Hold time message

D. OPEN message contains only BGP message header

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 43

Which of the following types of equipment is suitable for Huawei's IP wide area bearer network solution?

A. CE12804

B. AirEngine 5760-22w

C. NetEngine AR6000

D. NetEngine 8000

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 44

Regarding BGP MED, which of the following descriptions are correct? (Multiple choice)

A. By default, if the MED value is not set in the route attribute, press the process. If the bestroute med-none-as maximum command is configured. Then handle the maximum MED value of 4294967295

B. The default value of BGP route MED is 0

C. By default, BGP routing rules can compare the distance between routes from different autonomous systems.

D. In BGP routing rules, the priority of MED is lower than AS-Path, Preferred-Value, Local-Preference, Origin

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 45

BGP neighbors are neighbor relationships established through UDP.

A. FALSE

B. TRUE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 46

D. DoS attack means that the attacker controls a large number of zombie hosts and sends a large number of carefully constructed attack messages to the target network, so that the attacked has the effect of refusing to provide services to the requests of normal users.

A. False

B. True

Answer: B ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpsPass.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 47

Which of the following attributes meet the following conditions? The BCP router may not support these attributes, but it will still receive these attributes and pass them to other peers. (Multiple choice)

A. Ageregator

B. Community

C. Local_Pref

D. Multi_Exit_Disc

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 48

By default, for routers running IS-IS in a broadcast network, how many seconds does the DIS send CSNP packets?

A. 30

B. 10

C. 3.3

D. 40

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 49

In the N+1 backup network of WLAN, which of the following statements about option43 is correct? (Multiple choice)

- A.** If the AC of the IP address advertised by option 43 does not respond to the AP, the AP will find that the AC will immediately fail
 - B.** After the option 43 field is configured, the AP will only send unicast Discovery Request messages to the AC IP address advertised by option 43
 - C.** To configure the option 43 field, the AP needs to be notified of the IP addresses of the primary AC and backup AC to which it belongs, and also the IP addresses of other primary ACs.
 - D.** The command to configure the option43 parameter field of the DHCP server to the IP addresses of the primary and standby ACs is option43 sub-Option 2 ip-address ip-address &<1-8>
- Answer: B,D ([LEAVE A REPLY](#))**

NEW QUESTION: 50

Which one of the following descriptions of the trigger mechanism of 802.1X authentication is correct? (Multiple choice)

- A.** 802.1X clients can trigger authentication by multicast or broadcast
- B.** The authentication device can trigger authentication in multicast or unicast mode
- C.** 802.1X authentication cannot be initiated by an authentication device (such as an 802.1 switch)
- D.** 802.1X authentication can only be initiated by the client

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 51

Which of the following dynamic routing protocols can be applied to IPv6 networks? (Multiple choice)

- A.** Is-Is
- B.** BGP6
- C.** OSPFv3
- D.** IS-ISv6

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 52

As shown in the figure, the management VLAN of LAN is VLAN 10. AP obtains IP address through DHCP, and the network segment is 10.1. 1.0/24 AP, AC and AR are respectively DHCP client, DHCP relay device and DHCP server. (Multiple choice)

Which of the following is the correct configuration of the DHCP relay device and DHCP server?

- A.** [AR] ip pool AP [AR-ip pool-AP] network 10.1.1.0 mask 24 [AR-ip-pool-AP] gateway-list 10.1.1.2 [AR-ip-pool-AP] excluded ip-address 10.1.1.1 [AR-ip-pool-AP] quit [AR] interface GigabitEthernet 0/0/1 [AR-GigabitEthernet0/0/1] dhcp select global [AR-GigabitEthernet0/0/1] quit [AR] ip route-static 10.1.1.0 255.255.255.0 172.21. 1.1
- B.** [AR] ip pool AP [AR-ip-pool-AP] network 172.21.1.0 mask 24 [AR-ip-pool-AP] gateway-list 172.21.1.2 [AR-ip-pool-AP] excluded ip-address 172.21.1.1 [AR-ip-pool-AP] quit [AR] interface

GigabitEthernet 0/0/1 LAR-GigabitEthernet0/0/1] dhcp select global [AR-GigabitEthernet0/0/1] quit [AR]ip route-static 10.1.1.0 255.255.255.0 172.21.1.1

C. [Ac]dhcp server group AP [AC-dhcp-server-group-AP] dhcp-server 10.1.1.2 [AC-dhcp server group-AP] quit [AC] interface Vlanif 10 [AC-Vlanif10] dhcp select relay [AC-Vlanif10] dhcp relay server-select AP [AC-Vlanif10] quit

D. [AC] dhcp server group AP [AC-dhcp-server-group-AP] dhcp-server 172.21.1.2 [AC-dhcp-server-group-AP] quit [AC] interface Vlanif 10 [AC-Vlanif10] dhcp select relay [AC-Vlanif10] dhcp relay server-select AP [AC-Vlanif10] quit

Answer: A,D ([LEAVE A REPLY](#))

NEW QUESTION: 53

It is possible to prevent the HSB backup channel between the active and standby ACs from being interrupted and unperceivable through mechanisms such as sending active and standby service packets and retransmissions.

A. True

B. False

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 54

Which of the following description about the default routing of each protocol is wrong?

A. BGP can deliver default routes

B. Static default route can be configured

C. ISIS can issue default routes

D. OSPF cannot deliver default routes

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 55

The network administrator of a company checks the FIB of the router. What fields does the FIB contain? (Multiple choice)

A. Protocol

B. Cost

C. Destination/Mask

D. TimeStamp

Answer: C,D ([LEAVE A REPLY](#))

NEW QUESTION: 56

About LSA3, LSA4 and LSA5, which of the following description is true?

A. LSA3 will not change after traversing different areas, while LSA4 and LSA5 will change

B. LSA3, LSA4 and LSA5 will not change after traversing different areas

C. LSA4 will not change after traversing different areas, while LSA3 and LSA5 will change

D. LSA5 will not change after traversing different areas, while LSA3 will change

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 57

What are the routing tools that are not only used for the BGP routing protocol? (Multiple choice)

- A. IP-Prefix
- B. as-path-filter
- C. ACL
- D. community-filter

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 58

Which of the following descriptions of Link ID, Data, Type and Metric in Router-L SA are correct? (Multiple choice)

- A. Data is used to describe the additional information of this connection, and different connection types refer to different information
- B. Metric describes the cost of this connection
- C. Type indicates the type of connection
- D. Link ID represents the local identification of this connection, and the same connection type Link ID represents different meanings

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 59

Which routes in the following options meet the following ACL conditions? (Multiple choice)

- A. 10.1.2.1/32
- B. 10.1.3.1/32
- C. 10.1.4.1/32
- D. 10.1.1.1/32

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 60

In the network as shown in the figure, all switches run the RSTP protocol. If the E1 interface of SWB fails, when the RSTP process, then what will happen? (Multiple choice)

- A. Send topology change notifications (Topology Change Notification) on all forwarding ports to notify other switches that topology changes have occurred in the network
- B. Recalculate the spanning tree, SWB elects E2 as the root port
- C. SWB deletes the port entry of the port whose purpose is E1 in the MAC address table
- D. On all non-edge forwarding ports, send topology change notifications (Topology Change Notification) to notify other switches that topology changes have occurred in the network

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 61

Which port role that cannot be in the forwarding state in RSTP? (Multiple choice)

- A. Designated Port
- B. Alternate Port
- C. RootPort
- D. Backup Port

Answer: B,D ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpsPASS.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 62

Regarding BGP reliable routing updates, which of the following description of is ture?

- A. BGP uses multicast updates
- B. BGP does not need to periodically advertise routing information
- C. BGP works on top of UDP, and the transport layer protocol is 179
- D. BGP sends complete routing table information every time a route is updated

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 63

When two routers exchange database information through DD messages, a master-slave relationship is first formed, and the one with the larger router id must be the master.

- A. FALSE
- B. TRUE

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 64

For the link state routing protocol, when filter-policy import is used, the filtered link state information cannot be calculated as a route, and its neighbors cannot receive complete link state information.

- A. FALSE
- B. TRUE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 65

As shown in the figure, RTA, RTB, RTC, and RTD are in the same AS. IBGP neighbor relationships are established through direct links. RTB and RTC are route reflectors. RTA and RTC are the route reflector clients of RTB. RTD is the route reflector client of RTC, and 10.1.1.0/24 is announced into BGP on RTA, and the Originator ID value of the BGP route received on RTD is updated to ().

Answer:

1.1.1.1

NEW QUESTION: 66

Which of the following description about OSPF routing aggregation is wrong?

- A.** Through route aggregation, routing information can be reduced, thereby reducing the size of the routing table and improving the performance of the router
- B.** Inter-area route aggregation refers to the aggregation of routing information of the same prefix, and only one route is advertised to other areas
- C.** Any router in OSPF can perform route aggregation operations
- D.** OSPF has two route aggregation methods: ABR aggregation and ASBR aggregation

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 67

Which of the following Hello messages is not included in the IS-IS protocol?

- A.** P2PIIIH
- B.** Leve1-2 LANIIH
- C.** Leve1-1 LAN IH
- D.** P2MP IIH

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 68

In the RSTP protocol, when the network topology changes, the mechanism for responding to changes in the topology is?

- A.** Modify the lifetime of the MAC address table
- B.** Delete the entire MAC address table
- C.** The MAC table remains unchanged
- D.** Partial deletion of the MAC address table

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 69

The import-route limit command cannot limit the maximum number of external routes that can be imported in an OSPF process.

- A.** FALSE
- B.** TRUE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 70

Route redistribution refers to the operation of only advertising routing information from one routing protocol to another routing protocol.

Which of the following statements about route introduction is correct? (Multiple choice)

- A. When implementing route import, you need to pay attention to the routing priority agreements of different vendors may be different
- B. When implementing route import, route control can also be deployed to achieve flexible control of correct business traffic
- C. By importing routes, routing information can be transmitted between different routing protocols
- D. The routing protocol itself has anti-loop characteristics, so there is no need to consider loop issues when routes are imported into each other

Answer: A,B,C ([LEAVE A REPLY](#))

NEW QUESTION: 71

Which of the following about the IS-IS protocol statement is false?

- A. IS-IS protocol supports IP network
- B. IS-IS protocol packets are directly encapsulated by the data link layer
- C. IS-IS protocol supports CLNP network
- D. The Is-Is protocol is a link state protocol running between ASs

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 72

As shown in the figure, in the network running the RSTP protocol, the original root port of SWC fails and the port is in Down state. At this time, which of the following processes will the network go through to achieve stability?

- A. SWC re-elects the root port and directly enters the Forwarding state
- B. SWC re-elects the root port and enters the Forwarding state after passing through the Learning state
- C. The standby port on the SWC becomes the new root port and enters the Forwarding state after passing through the Learning state
- D. The standby port on the SWC becomes the new root port and directly enters the Forwarding state

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 73

As show in the figure, which of the following statements is true?

- A. R1 and 2 cannot establish adjacency, because the network type of the interface is not consistent
- B. R1 and R2 cannot establish adjacency, because OSPF process ID is not consistent
- C. R1 and R2 can establish adjacency and can complete routing calculations

D. R1 and R2 can establish adjacency, but cannot complete routing calculations

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 74

The command to configure VRRP preemption delay is:

- A. vrrp twist 1 hour delay 20
- B. vrrp vrid 1 preempt-delay 20
- C. vrrp vrid 1 preempt-mode timer delay 20
- D. vrrp vrid 1 preempt-timer 20

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 75

The four routers are running IS-S and have established adjacency. The area number and router level are marked as shown in the figure. What is the cost value from R4 to 10.0.2.2/32?

- A. 40
- B. 20
- C. 10
- D. 30

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 76

Which of the following descriptions of the OSPF protocol are correct? (Multiple choice)

- A. AS-External-LSA does not belong to any area
- B. AS-External-LSA describes the flooding scope of the route to the AS external route is outside the AS
- C. The cost value of the second type of external route is only the AS external cost value, and the AS internal cost value is ignored
- D. AS-External-LSA describes the path from the router to the ASBR

Answer: A,C ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpsPass.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 77

The MQC traffic behavior supports multiple actions on messages. Please match the actions of the following MQC traffic behaviors with their functions.

Answer:

NEW QUESTION: 78

Which of the following description about the way of BFD session establish is wrong?

- A. The system distinguishes between static BFD sessions and dynamic BFD sessions by dividing the identifier area.
- B. When a BFD session is dynamically established, the local identifier is dynamically allocated.
- C. Statically configuring a BFD session refers to configuring BFD session parameters through the command line, including local identifiers and remote identifiers, etc.
- D. BFD sessions can only be established dynamically

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 79

A switch runs the RSTP protocol, and its related configuration information is shown in the figure. According to the command configuration, please point out that for Instance 1, the role of the switch is:

- A. Unable to judge
- B. Root switch
- C. Non-root switch
- D. Switch

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 80

When the Hold time supported by two BGP neighbors is inconsistent, the neighbors will negotiate to adopt the lowest Hold time interval that both ends can support.

- A. FALSE
- B. TRUE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 81

In a stateful inspection firewall, when the stateful inspection mechanism is turned on, when the second packet (SHN+ACK) of the three-way handshake arrives at the firewall, if there is no corresponding session table on the firewall, which of the following statements is correct?

- A. If the firewall security policy allows packets to pass, create a session table
- B. If the firewall security policy allows packets to pass, the packets can pass through the firewall
- C. The message must pass through the firewall and establish a session table
- D. By default, after the status function is turned off, and the permission policy is configured, you can pass

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 82

When using a routing policy for route filtering, which routes the prefix of the following options in matching the following IP-Prefix will be denied out? (Multiple choice)

[HUAWEI] ip ip-prefix aa index 10 deny 0.0.0.0 24 less-equal 32

[HUAWEI] ip ip-prefix aa index 20 permit 0.0.0.0 0 less-equal 32

A. 1.1.1.1/32

B. 1.1.1.1/26

C. 1.1.1.2/16

D. 1.1.1.1/24

Answer: A,B,D ([LEAVE A REPLY](#))

NEW QUESTION: 83

To achieve the traffic filtering function, can use traffic-filter or MQC. Compared with traffic-filter, MQC can be called in more views.

A. True

B. False

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 84

Which protocol modules can BFD detection be linked with? (Multiple choice)

A. OSPF

B. BGP

C. Static routing

D. VRRP

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 85

The network is as shown in the figure, and SWA, SWB, SWC, and SWD run RSTP, then which of the following statement is correct? (Multiple choice)

A. The edge port can be opened on the GE0/0/2 port of SWB, so that the interface connected to the terminal can quickly enter the forwarding state

B. The edge port can be opened on the GE0/0/2 port of SWC, so that the interface connected to the terminal can quickly enter the forwarding state

C. After being configured as an edge port, the interface can quickly enter the forwarding state

D. After receiving the BPDU, the edge port will participate in the calculation of the spanning tree again

Answer: B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 86

OSPF can support multiple network types. Which of the following network types need to elect DR and BDR? (Multiple choice)

- A. P2P
- B. NBMA
- C. ROADCAST
- D. P2MP

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 87

The default value of the ospfdr-priority command is 1, and the value range is 0~255.

- A. TRUE
- B. FALSE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 88

The edge port in RSTP does not need to wait for the forwarding delay, and can directly enter the forwarding state. If the edge port receives the BPDU, the edge port will be directly closed and enter the error down state.

- A. True
- B. False

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 89

If the router-id is configured in both the system view and the BGP view of the router, because the BGP view has a higher priority, BGP uses the router-id in the BGP view.

- A. FALSE
- B. TRUE

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 90

Which of following description of the permanent multicast address is wrong?

- A. All hosts and routers in the network segment monitor 224.0.0.1
- B. All routers running the PIM protocol monitor 224.0.0.100
- C. All routers monitor 224.0.0.2
- D. All routers running OSPF protocol monitor 224.0.0.5

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 91

Which of the following statement about equipment for the exchange of forwarding plane is incorrect?

- A. Statistics of messages can be realized

- B. Realize packet encapsulation and decapsulation
- C. Composed of main control board and interface board
- D. Provide high-speed non-blocking data channels

Answer: C ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:
https://www.braindumpsPASS.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html
(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 92

MQC, like PBR, can only be called under the three-layer interface of the device.

- A. TRUE
- B. FALSE

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 93

Regarding the OSPF multi-process description, which is wrong?

- A. Multiple different OSPF processes can run on the same router, and they do not affect each other and are independent of each other
- B. Different OSPF routers establish neighbors, and the process numbers must be the same
- C. An interface of a router can only belong to one OSPF process
- D. The routing interaction between different OSPF processes is equivalent to the routing interaction between different routing protocols

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 94

A network engineer outputs the following information when troubleshooting the OSPF protocol. Based on this to determine which cause the adjacency relationship cannot be established normally?

- A. Router ID conflict
- B. Process numbers are discordance
- C. The IP address code of the interface is discordance
- D. The area code does not match

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 95

Regarding the ABR in OSPF, which of the following description is wrong?

- A. The Type 1, Type 2, and Type 3 LSA in the backbone area of the ABR are converted to Type 3 LSA and published to the connected non-skeletal area
- B. Convert the Type 1 and Type 2 LSAs in the connected non-skeletal area into Type 3 LSAs and publish them to the backbone area
- C. There are multiple LSDBs on the ABR, and the ABR maintains one LSDB for each area
- D. ABR cannot generate Type 3, Type 4, or Type 5 LSA

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 96

When two devices with the same priority compete for the role of Master at the same time, the device with the interface with the smaller IP address should be selected as the Master device

- A. TRUE
- B. FALSE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 97

If IGP routing wants to become a BGP routing, it can only be done through the network command.

- A. True
- B. False

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 98

When the payload is an ICMPv6 packet, if the extended header is not considered, what is the value of the Next Header field in the IPv6 header?

- A. 78
- B. 55
- C. 68
- D. 58

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 99

Which of the following descriptions of MED is correct? (Multiple choice)

- A. The default value of MED is 0
- B. MED is an optional non-transitional attribute
- C. The default value of MED is 100
- D. MED can only be delivered within this AS

Answer: A,B ([LEAVE A REPLY](#))

NEW QUESTION: 100

In the description of the default priority of each protocol under the VRP platform, which is correct?

- A. The priority of ISIS routing is 10
- B. The priority of OSPF routing is 15
- C. The priority of static routing is 60
- D. The priority of BGP routing is 20

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 101

The three routers are running IS-IS and have established adjacency relationships. The area numbers and router levels are marked as shown in the figure. If the road between R1 and R2 is interrupted, which of the following statements is correct? (Multiple choice)

- A. R1 runs the SPF algorithm to delete R2 from the SPF trunk
- B. The default route in the R2 routing table still exists
- C. The default route in the R2 routing table will disappear
- D. R1 sets the Age of the L SP generated by R2 to 0

Answer: A,C ([LEAVE A REPLY](#))

NEW QUESTION: 102

Option 82 in the DHCP message is called the relay agent information option, from which the administrator can obtain a lot of information about the client. Option 82 can contain at most () Sub-Options.

Answer:

255

NEW QUESTION: 103

OSPF supports area authentication and interface authentication. If both authentication methods are configured at the same time, interface authentication is better than area authentication.

- A. FALSE
- B. TRUE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 104

IGMP Snooping cannot solve the bandwidth waste of multicast traffic on the Layer 2 switch, that is, whether IGMP Snooping is configured on the Layer 2 switch has no effect on the multicast traffic.

- A. FALSE
- B. TRUE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 105

Regarding the description of the permanent multicast address, which of the following is false?

- A. All hosts and routers in the network segment listen to 224.0.0.1
- B. All routers listen on 224.0.0.2
- C. All routers running the PIM protocol listen to 224.0.0.100
- D. All routers running OSPF protocol listen on 224.0.0.5

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 106

The following is a router BGP error output information, which description of this information is wrong?

<HUAWEI>display bgp error Error Type: Peer Error Date/Time:2010-03-22 11:40:39 Peer Address:10.1.1.2 Error Info Router-id conflict

- A. Error Type display because the neighbor relationship False caused
- B. The error occurred at 11:40:39 on March 22, 2010
- C. False may be caused by the wrong AS number of the peer
- D. The router's neighbor address is 10.1.1.2.

Answer: C ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpsPASS.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 107

Which of the following statements about the OSPF protocol is wrong?

- A. OSPF supports load sharing for equal-cost routes
- B. OSPF is an exterior gateway protocol based on link state
- C. OSPF packets are encapsulated in IP packets and can be sent in the form of unicast or multicast
- D. OSPF protocol supports area division

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 108

The router directly instructs the forwarding of data according to the forwarding table.

- A. False
- B. True

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 109

One of the features of OSPF is that it only supports MD5 authentication.

- A. True
- B. False

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 110

Which of the following attacks is not a network layer attack?

- A. A RP spoofing attack
- B. ICMP attack
- C. Smurf attack
- D. IP spoofing attack

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 111

The interface IP address and virtual IP address of VRRP can be the same

- A. FALSE
- B. TRUE

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 112

Which of the following LSAs only spread in a single area? (Multiple choice)

- A. Network LSA
- B. RouterLSA
- C. AS ExternalLSA
- D. Summary LSA

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 113

What are the conditions for matching firewall security policies? (Multiple choice)

- A. Source and destination security zone
- B. Source and destination IP address
- C. Application
- D. Packet length

Answer: A,B,C ([LEAVE A REPLY](#))

NEW QUESTION: 114

Which of the following description of roaming is correct? (Multiple choice)

- A. APs that implement wireless roaming do not need to have signal coverage overlapping areas

- B. APs that implement wireless roaming must have signal coverage overlapping areas
- C. APs that implement wireless roaming must be in the same extended service set (ESS)
- D. APs that implement wireless roaming must be in the same basic service set (BSS)

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 115

What are the benefits of OSPF area division? (Multiple choice)

- A. Routers in an area can understand the topology details outside their area
- B. It can reduce the size of LSDB and thus reduce the consumption of router memory
- C. A large number of LSA flooding is restricted to a single area
- D. LSA can also be reduced with the division of areas, reducing the consumption of router CPU

Answer: B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 116

Which of the following categories can ACL be divided into? (Multiple choice)

- A. Layer 2 ACL
- B. Basic ACL
- C. Advanced ACL
- D. User-defined ACL

Answer: A,B,C,D ([LEAVE A REPLY](#))

NEW QUESTION: 117

Which of the following description of roaming is wrong? (Multiple choice)

- A. When roaming, the STA that associates with the new AP sends a re-association request and contains the information of the original associated AP
- B. When roaming, the STA that associates with the new AP sends an association request and contains the information of the original associated AP
- C. The working channels of the two APs before and after the immersion can be different
- D. The working channels of the two APs before and after roaming must be the same

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 118

The content contained in the UPDATE message, which of the description is wrong?

- A. UPDATE contains path attributes
- B. UPDATE contains reachable route prefix information
- C. UPDATE contains information about withdrawing the routing prefix
- D. UPDATE contains the local AS number

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 119

Modify which of the following parameters, IS-IS neighbor relationship needs to be re-established?
(Multiple choice)

- A. Modify the sending interval of IIH on the IS-IS interface
- B. Modify the cost value of the IS-IS interface
- C. Modify the IF address of the IS-IS interface
- D. Modify the level of the IS-IS interface

Answer: (SHOW ANSWER)

NEW QUESTION: 120

The following information is output to a route, which of the following description about the information is correct?

- A. The Router ID of the router is 1.1.1.1
- B. The AS number where the router is located is 100
- C. The router negotiates with its neighbors and uses BGP version 3
- D. The router has an IBGP neighbor relationship with neighbor 2.2.2.2

Answer: B (LEAVE A REPLY)

NEW QUESTION: 121

Which of the following tools is used to filter routing information and set routing attributes for the routing information that passes the filter?

- A. IP-prefix
- B. policy-based-route
- C. as-path-filter
- D. route-policy

Answer: (SHOW ANSWER)

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpsPASS.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)

NEW QUESTION: 122

Which of the following descriptions are correct about two-tier roaming and three-tier roaming?
(Multiple choice)

- A. Layer 2 roaming means that the client roams in the same subnet

- B.** The VLANs on the AP service set associated with the STA before and after Layer 3 roaming must be the same
- C.** If the VLAN ID associated before and after the STA is the same when roaming, it must belong to Layer 2 roaming
- D.** Three-tier roaming means that the client roams between different subnets

Answer: B,D ([LEAVE A REPLY](#))

NEW QUESTION: 123

How many Bytes is the minimum total length of the address in IS-IS?

- A.** 8
- B.** 20
- C.** 16
- D.** 2

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 124

In the routing rules of BGP, the manually aggregated route generated by the aggregate command has a higher priority than the automatically aggregated route generated by the summary automatic command.

- A.** TRUE
- B.** FALSE

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 125

Which of the following description of the prefix list is wrong?

- A.** The prefix list can match the prefix number and prefix length
- B.** The prefix list has a stronger matching function for the routing mask than the access control list
- C.** The prefix list can be used for packet filtering
- D.** The prefix list can be used to filter IP prefixes

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 126

The role of the switch in the stacking system not include:

- A.** Slave switch
- B.** Main switch
- C.** Candidate switch
- D.** Standby switch

Answer: ([SHOW ANSWER](#)**)**

NEW QUESTION: 127

In the IS-IS broadcast network, which multicast MAC address does the Level-2 router use as the destination address for sending IH?

- A. 0100-5E00-0002
- B. 0180-c200-0016
- C. 0180-c200-0015
- D. 0180-c200-0014

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 128

The following description of the BGP UPDATE message, which is wrong?

- A. The UPDATE message is sent in the form of multicast
- B. UPDATE message is used to transfer routing information between BGP peers
- C. Generally, the UPDATE message is sent after Keepalive
- D. UPDATE message can carry multiple reachable routing information

Answer: A ([LEAVE A REPLY](#))

Valid H12-821_V1.0-ENU Dumps shared by BraindumpsPass.com for Helping Passing H12-821_V1.0-ENU Exam! BraindumpsPass.com now offer the **newest H12-821_V1.0-ENU exam dumps**, the BraindumpsPass.com H12-821_V1.0-ENU exam **questions have been updated** and **answers have been corrected** get the **newest** BraindumpsPass.com H12-821_V1.0-ENU dumps with Test Engine here:

https://www.braindumpspass.com/Huawei/H12-821_V1.0-ENU-practice-exam-dumps.html

(1081 Q&As Dumps, **40%OFF** Special Discount: **Exam-Tests**)